



# Guía de instalación Pandora FMS en Rocky Linux



<https://pandorafms.com/manual/!775/>

Permanent link:

[https://pandorafms.com/manual/!775/es/documentation/pandorafms/technical\\_annexes/31\\_pfms\\_install\\_latest\\_rocky\\_linux](https://pandorafms.com/manual/!775/es/documentation/pandorafms/technical_annexes/31_pfms_install_latest_rocky_linux)

4/03/18 21:03



# Guía de instalación Pandora FMS en Rocky Linux

## Requisitos previos

- Rocky Linux 8 con derechos de usuario root.
- Conexión a internet.

## Configuración de repositorios

```
dnf install -y \  
  epel-release \  
  tar \  
  dnf-utils \  
  http://rpms.remirepo.net/enterprise/remi-release-8.rpm
```

```
dnf module reset php  
  
dnf module install -y php:remi-8.0  
  
dnf config-manager --set-enabled powertools
```

## Instalación de base de datos Percona

```
dnf install -y https://repo.percona.com/yum/percona-release-latest.noarch.rpm  
  
dnf module disable -y mysql  
  
rm -rf /etc/my.cnf  
  
percona-release setup ps80 -y  
  
dnf install -y percona-server-server percona-xtrabackup-80
```

## Instalación de dependencias de Consola web

```
dnf install -y \  
  php \  
  postfix \  
  php-mcrypt \  
  php-cli \  
  php-gd \  
  php-ldap
```

```
php-curl \  
php-session \  
php-mysqlnd \  
php-ldap \  
php-zip \  
php-zlib \  
php-fileinfo \  
php-gettext \  
php-snmp \  
php-mbstring \  
php-pecl-zip \  
php-xmllrpc \  
libxslt \  
wget \  
php-xml \  
httpd \  
mod_php \  
atk \  
avahi-libs \  
cairo \  
cups-libs \  
fribidi \  
gd \  
gdk-pixbuf2 \  
ghostscript \  
graphite2 \  
graphviz \  
gtk2 \  
harfbuzz \  
hicolor-icon-theme \  
hwdata \  
jasper-libs \  
lcms2 \  
libICE \  
libSM \  
libXaw \  
libXcomposite \  
libXcursor \  
libXdamage \  
libXext \  
libXfixes \  
libXft \  
libXi \  
libXinerama \  
libXmu \  
libXrandr \  
libXrender \  
libXt \  
libXxf86vm \  
libcroco \  
libdrm \  
libfontenc \  

```

```
libglvnd \  
libglvnd-egl \  
libglvnd-glx \  
libpciaccess \  
librsvg2 \  
libthai \  
libtool-ltdl \  
libwayland-client \  
libwayland-server \  
libxshmfence \  
mesa-libEGL \  
mesa-libGL \  
mesa-libgbm \  
mesa-libglapi \  
pango \  
pixman \  
xorg-x11-fonts-75dpi \  
xorg-x11-fonts-misc \  
poppler-data \  
php-yaml \  
mod_ssl \  
libzstd \  
openldap-clients \  
http://firefly.pandorafms.com/centos8/chromium-110.0.5481.177-1.el7.x86_64.rpm \  
http://firefly.pandorafms.com/centos8/chromium-common-110.0.5481.177-1.el7.x86_64.rpm \  
http://firefly.pandorafms.com/centos8/perl-Net-Telnet-3.04-1.el8.noarch.rpm \  
http://firefly.pandorafms.com/centos7/wmic-1.4-1.el7.x86_64.rpm
```

## Instalación de dependencias de PFMS server

```
dnf install -y \  
perl \  
vim \  
fping \  
perl-IO-Compress \  
nmap \  
sudo \  
perl-Time-HiRes \  
nfdump \  
net-snmp-utils \  
'perl(NetAddr::IP)' \  
'perl(Sys::Syslog)' \  
'perl(DBI)' \  
'perl(XML::Simple)' \  
'perl(Geo::IP)' \  
'perl(IO::Socket::INET6)' \  
'perl(XML::Twig)' \  
expect
```

```
openssh-clients \  
java \  
bind-utils \  
whois \  
http://firefly.pandorafms.com/centos7/xprobe2-0.3-12.2.x86_64.rpm \  
http://firefly.pandorafms.com/centos7/wmic-1.4-1.el7.x86_64.rpm \  
https://firefly.pandorafms.com/centos8/pandorawmic-1.0.0-1.x86_64.rpm
```

## Dependencias de Perl y VMware

```
dnf install -y \  
perl-Net-HTTP \  
perl-libwww-perl \  
openssl-devel \  
perl-Crypt-CBC \  
perl-Bytes-Random-Secure \  
perl-Crypt-Random-Seed \  
perl-Math-Random-ISAAC \  
perl-JSON \  
perl-Crypt-SSLeay \  
http://firefly.pandorafms.com/centos8/perl-Crypt-OpenSSL-AES-0.02-1.el8.x86_64.r  
pm \  
http://firefly.pandorafms.com/centos8/VMware-vSphere-Perl-SDK-6.5.0-4566394.x86_  
64.rpm
```

## Instalación del cliente Oracle

```
dnf install -y \  
https://download.oracle.com/otn_software/linux/instantclient/19800/oracle-instan  
tclient19.8-basic-19.8.0.0.0-1.x86_64.rpm \  
https://download.oracle.com/otn_software/linux/instantclient/19800/oracle-instan  
tclient19.8-sqlplus-19.8.0.0.0-1.x86_64.rpm
```

## Instalación de dependencias para Discovery PFMS

```
curl https://packages.microsoft.com/config/rhel/8/prod.repo -o  
/etc/yum.repos.d/mssql-release.repo
```

```
dnf remove unixODBC-utf16 unixODBC-utf16-devel
```

```
env ACCEPT_EULA=Y dnf install -y msodbcsql17
```

## Ajustes del sistema operativo y creación de base de datos

```
setenforce 0
```

```
sed -i -e "s/^SELINUX=.*SELINUX=disabled/g" /etc/selinux/config  
systemctl disable firewalld --now
```

---

```
cat> /etc/my.cnf <<EO_CONFIG_TMP  
[mysqld]  
datadir=/var/lib/mysql  
socket=/var/lib/mysql/mysql.sock  
symbolic-links=0  
log-error=/var/log/mysql.log  
pid-file=/var/run/mysql/mysql.pid  
EO_CONFIG_TMP
```

---

```
systemctl start mysqld  
  
grep "temporary password" /var/log/mysql.log | rev | cut -d' ' -f1 | rev  
mysql -uroot -p"contraseña";  
  
SET PASSWORD FOR 'root'@'localhost' = 'Pandora4!';  
  
UNINSTALL COMPONENT 'file://component_validate_password';  
  
SET PASSWORD FOR 'root'@'localhost' = 'pandora';  
  
CREATE DATABASE pandora;  
  
CREATE USER 'pandora'@'%' IDENTIFIED BY 'pandora';  
  
ALTER USER 'pandora'@'%' IDENTIFIED WITH mysql_native_password BY 'pandora';  
GRANT ALL PRIVILEGES ON pandora.* TO 'pandora'@'%';  
  
exit
```

---

```
POOL_SIZE=$(grep -i total /proc/meminfo | head -1 | awk '{printf "%.2f \n",  
$(NF-1)*0.4/1024}') | sed "s/\\..*$/M/g")
```

---

```
cat> /etc/my.cnf <<EO_CONFIG_F  
[mysqld]  
datadir=/var/lib/mysql  
socket=/var/lib/mysql/mysql.sock  
user=mysql  
character-set-server=utf8mb4  
skip-character-set-client-handshake  
# Disabling symbolic-links is recommended to prevent assorted security risks
```

```
symbolic-links=0
# Mysql optimizations for Pandora FMS
# Please check the documentation in http://pandorafms.com for better results

max_allowed_packet = 64M
innodb_buffer_pool_size = $POOL_SIZE
innodb_lock_wait_timeout = 90
innodb_file_per_table
innodb_flush_log_at_trx_commit = 0
innodb_flush_method = O_DIRECT
innodb_log_file_size = 64M
innodb_log_buffer_size = 16M
innodb_io_capacity = 300
thread_cache_size = 8
thread_stack      = 256K
max_connections = 100

key_buffer_size=4M
read_buffer_size=128K
read_rnd_buffer_size=128K
sort_buffer_size=128K
join_buffer_size=4M

skip-log-bin

sql_mode=""

[mysqld_safe]
log-error=/var/log/mysqld.log
pid-file=/var/run/mysqld/mysqld.pid

EO_CONFIG_F
```

```
systemctl restart mysqld

systemctl enable mysqld --now
```

---

## Instalación de la Consola y Pandora FMS server

```
wget
https://firefly.pandorafms.com/pandorafms/latest/RHEL_CentOS/pandorafms_agent_linux-7.0NG.noarch.rpm

wget
https://firefly.pandorafms.com/pandorafms/latest/RHEL_CentOS/pandorafms_console-7.0NG.noarch.rpm
```



```
wget
https://firefly.pandorafms.com/pandorafms/latest/RHEL_CentOS/pandorafms_server-7
.0NG.noarch.rpm
```

---

```
dnf install -y ./pandorafms*.rpm
```

---

```
wget https://firefly.pandorafms.com/pandorafms/utils/gotty_linux_amd64.tar.gz
tar xvzf gotty_linux_amd64.tar.gz
mv gotty /usr/bin/
```

---

```
systemctl enable mysqld --now
systemctl enable httpd --now
```

---

```
mysql -upandora -ppandora
```

```
use pandora;
source /var/www/html/pandora_console/pandoradb.sql;
source /var/www/html/pandora_console/pandoradb_data.sql;
exit;
```

---

```
cat> /var/www/html/pandora_console/include/config.php <<EO_CONFIG_F
<?php
$config["dbtype"] = "mysql";
$config["dbname"]="pandora";
$config["dbuser"]="pandora";
$config["dbpass"]="pandora";
$config["dbhost"]="127.0.0.1";
$config["homedir"]="/var/www/html/pandora_console";
$config["homeurl"]="/pandora_console";
error_reporting(0);
$ownDir = dirname(__FILE__) . '/';
include ($ownDir . "config_process.php");
EO_CONFIG_F
```

---

```
cat> /etc/httpd/conf.d/pandora.conf <<EO_CONFIG_F
<Directory "/var/www/html">
Options Indexes FollowSymLinks
AllowOverride All
Require all granted
</Directory>
EO_CONFIG_F
```

---

```
cat>> /etc/httpd/conf.modules.d/00-proxy.conf <<'EO_HTTPD_MOD'
LoadModule proxy_wstunnel_module modules/mod_proxy_wstunnel.so

EO_HTTPD_MOD
```

---

```
cat>> /etc/httpd/conf.d/wstunnel.conf <<'EO_HTTPD_WSTUNNEL'
ProxyRequests Off
<Proxy *>
    Require all granted
</Proxy>

ProxyPass /ws ws://127.0.0.1:8080
ProxyPassReverse /ws ws://127.0.0.1:8080

EO_HTTPD_WSTUNNEL
```

---

```
sed -i -e "s/php_flag engine off//g"
/var/www/html/pandora_console/images/.htaccess

sed -i -e "s/php_flag engine off//g"
/var/www/html/pandora_console/attachment/.htaccess
```

---

```
chmod 600 /var/www/html/pandora_console/include/config.php

chown apache. /var/www/html/pandora_console/include/config.php

mv /var/www/html/pandora_console/install.php
/var/www/html/pandora_console/install.done
```

---

```
sed -i -e "s/^max_input_time.*/max_input_time = -1/g" /etc/php.ini
sed -i -e "s/^max_execution_time.*/max_execution_time = 0/g" /etc/php.ini
sed -i -e "s/^upload_max_filesize.*/upload_max_filesize = 800M/g" /etc/php.ini
```

```
sed -i -e "s/^memory_limit.*/memory_limit = 800M/g" /etc/php.ini  
sed -i -e "s/.*post_max_size =.*/post_max_size = 800M/" /etc/php.ini
```

---

```
echo 'Timeout 900'> /etc/httpd/conf.d/timeout.conf  
cat> /var/www/html/index.html <<EOF_INDEX  
<meta HTTP-EQUIV="REFRESH" content="0; url=/pandora_console/">  
EOF_INDEX
```

---

```
systemctl restart httpd  
systemctl restart php-fpm
```

---

```
cat> /etc/snmp/snmptrapd.conf <<EOF  
authCommunity log public  
disableAuthorization yes  
EOF
```

---

```
sed -i -e "s/^dbhost.*/dbhost 127.0.0.1/g" /etc/pandora/pandora_server.conf  
sed -i -e "s/^dbname.*/dbname pandora/g" /etc/pandora/pandora_server.conf  
sed -i -e "s/^dbuser.*/dbuser pandora/g" /etc/pandora/pandora_server.conf  
sed -i -e "s|^dbpass.*|dbpass pandora|g" /etc/pandora/pandora_server.conf  
sed -i -e "s/^dbport.*/dbport 3306/g" /etc/pandora/pandora_server.conf  
sed -i -e "s/^#.mssql_driver.*/mssql_driver ODBC Driver 17 for SQL Server/g"  
/etc/pandora/pandora_server.conf
```

---

```
sed -i -e "s|^fping.*|fping /usr/sbin/fping|g" /etc/pandora/pandora_server.conf
```

---

```
sed -i "s/^remote_config.*$/remote_config 1/g" /etc/pandora/pandora_server.conf
```

---

```
cat> /etc/pandora/pandora_server.env <<'EOF_ENV'  
#!/bin/bash
```

```
VERSION=19.8
export PATH=$PATH:$HOME/bin:/usr/lib/oracle/$VERSION/client64/bin
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/usr/lib/oracle/$VERSION/client64/lib
export ORACLE_HOME=/usr/lib/oracle/$VERSION/client64
EOF_ENV
```

---

```
cat>> /etc/sysctl.conf <<E0_K0
# Pandora FMS Optimization

# default=5
net.ipv4.tcp_syn_retries = 3

# default=5
net.ipv4.tcp_synack_retries = 3

# default=1024
net.ipv4.tcp_max_syn_backlog = 65536

# default=124928
net.core.wmem_max = 8388608

# default=131071
net.core.rmem_max = 8388608

# default = 128
net.core.somaxconn = 1024

# default = 20480
net.core.optmem_max = 81920

E0_K0
```

---

```
sysctl --system

chown pandora:apache /var/log/pandora

chmod g+s /var/log/pandora
```

---

```
cat> /etc/logrotate.d/pandora_server <<E0_LR
/var/log/pandora/pandora_server.log
/var/log/pandora/web_socket.log
/var/log/pandora/pandora_server.error {
    su root apache
    weekly
    missingok
    size 300000
```

```
rotate 3
maxage 90
compress
notifempty
copytruncate
create 660 pandora apache
}

/var/log/pandora/pandora_snmptrap.log {
su root apache
weekly
missingok
size 500000
rotate 1
maxage 30
notifempty
copytruncate
create 660 pandora apache
}

EO_LR

cat> /etc/logrotate.d/pandora_agent <<EO_LRA
/var/log/pandora/pandora_agent.log {
su root apache
weekly
missingok
size 300000
rotate 3
maxage 90
compress
notifempty
copytruncate
}

EO_LRA
```

---

```
chmod 0644 /etc/logrotate.d/pandora_server
```

```
chmod 0644 /etc/logrotate.d/pandora_agent
```

---

```
systemctl enable pandora_server --now
```

```
/etc/init.d/pandora_server start
```

```
systemctl enable tentacle_serverd
```

```
service tentacle_serverd start
```

```
echo \"* * * * * root wget -q -O - --no-check-certificate --load-cookies  
/tmp/cron-session-cookies --save-cookies /tmp/cron-session-cookies --keep  
session-cookies http://127.0.0.1/pandora_console/enterprise/cron.php>>  
/var/www/html/pandora_console/log/cron.log\">> /etc/crontab
```

```
systemctl enable pandora_agent_daemon  
  
systemctl start pandora_agent_daemon
```

## Inicio de sesión en PFMS

Para acceder a la Consola web se ha de escribir la dirección IP (o URL) del dispositivo seguido de /pandora\_console/ .

Las credenciales por defecto para entrar son:

- usuario: admin
- contraseña: pandora

[Volver al índice de documentación de Pandora FMS](#)