



Pandora FMS installation guide on Ubuntu server



<https://pandorafms.com/manual/!current/>

Permanent link:

https://pandorafms.com/manual/!current/en/documentation/pandorafms/technical_annexes/30_pfms_install_latest_ubuntu_server

2023/04 21:28





Pandora FMS installation guide on Ubuntu server

We are working on the translation of the Pandora FMS documentation. Sorry for any inconvenience.

Prerequisites

- Ubuntu server 22.04 with root. user rights
- Internet connection.

Basic tools

In a terminal window with user root:

```
apt install -y gawk sed grep
```

```
rm -rf /opt/pandora/deploy
mkdir -p /opt/pandora/deploy
cd /opt/pandora/deploy
```

```
apt update
apt install -y net-tools vim curl wget \
  software-properties-common apt-transport-https \
  ca-certificates gnupg lsb-release
```

Apache2 and PHP 8

```
add-apt-repository ppa:ondrej/php
apt update
apt upgrade
apt install -y php8.0-fpm php8.0-common libapache2-mod-fcgid php8.0-cli apache2
a2enmod proxy_fcgi setenvif
systemctl reload apache2
a2enconf php8.0-fpm
systemctl restart php8.0-fpm
```



PFMS Web Console Dependencies

```
apt install -y \  
  ldap-utils postfix \  
  wget graphviz \  
  xfonts-75dpi xfonts-100dpi \  
  xfonts-ayu xfonts-intl-arabic \  
  xfonts-intl-asian xfonts-intl-phonetic \  
  xfonts-intl-japanese-big xfonts-intl-european \  
  xfonts-intl-chinese xfonts-intl-japanese \  
  xfonts-intl-chinese-big libzstd1 \  
  gir1.2-atk-1.0 libavahi-common-data \  
  cairo-perf-utils libfribidi-bin \  
  php8.0-mcrypt php8.0-gd \  
  php8.0-curl php8.0-mysql \  
  php8.0-ldap php8.0-fileinfo \  
  php8.0-gettext php8.0-snmp \  
  php8.0-mbstring php8.0-zip \  
  php8.0-xml rpc php8.0-xml \  
  php8.0-yaml libnet-telnet-perl \  
  whois cron
```

PFMS Server Dependencies

```
apt install -y \  
  perl nmap \  
  fping sudo \  
  net-tools nfdump \  
  expect openssh-client \  
  postfix unzip \  
  xprobe coreutils \  
  libmoosex-role-timer-perl libmoosex-perl \  
  libdbd-mysql-perl libcrypt-mysql-perl \  
  libhttp-request-ascgi-perl liblwp-useragent-chicaching-perl \  
  liblwp-protocol-https-perl snmp \  
  libnetaddr-ip-perl libio-socket-ssl-perl \  
  libio-socket-socks-perl libio-socket-ip-perl \  
  libio-socket-inet6-perl libnet-telnet-perl \  
  libjson-perl libencode-perl \  
  cron libgeo-ip-perl \  
  arping snmp-mibs-downloader \  
  openjdk-8-jdk
```

```
mkdir -m 0755 -p /etc/apt/keyrings
```

```
curl -fsSL https://download.docker.com/linux/ubuntu/gpg | \  

```

```
sudo gpg --yes --dearmor -o /etc/apt/keyrings/docker.gpg

threw out \
"deb [arch=$(dpkg --print-architecture) signed-
by=/etc/apt/keyrings/docker.gpg] https://download.docker.com/linux/ubuntu
$(lsb_release -cs) stable" | \
sudo tee /etc/apt/sources.list.d/docker.list

apt update -y
apt-get install -y \
docker-ce docker-ce-cli containerd.io \
docker-buildx-plugin docker-compose-plugin

systemctl disable docker --now
systemctl disable docker.socket --now
```

Dependencies to monitor by WMI

```
curl -O https://firefly.pandorafms.com/pandorafms/utils/bin/wmic
curl -O https://firefly.pandorafms.com/pandorafms/utils/bin/pandorawmic
chmod +x pandorawmic wmic
cp -a wmic /usr/bin/
cp -a pandorawmic /usr/bin/
```

Fping

```
rm -f /usr/sbin/fping
ln -s /usr/bin/fping /usr/sbin/fping
```

Google Chrome Tool

```
wget https://dl.google.com/linux/direct/google-chrome-stable_current_amd64.deb
dpkg -i google-chrome-stable_current_amd64.deb
ln -s /usr/bin/google-chrome /usr/bin/chromium-browser
```

VMware Tool

```
apt install -y \
lib32z1 lib32z1 \
build-essential uuid uuid-dev \
```

```
libssl-dev perl-doc \  
libxml-libxml-perl libcrypt-ssleay-perl \  
libsoap-lite-perl libmodule-build-perl  
wget  
https://firefly.pandorafms.com/pandorafms/utils/VMware-vSphere-Perl-SDK-7.0.0-16  
453907.x86_64.tar.gz  
tar -xzvf VMware-vSphere-Perl-SDK-7.0.0-16453907.x86_64.tar.gz  
cd vmware-vsphere-cli-distrib/  
sed --follow-symlinks -i -e "s/[^#].*show_EULA().*/ #show_EULA();/g" vmware-  
install.pl  
./vmware-install.pl -default  
cd ..
```

Oracle client tool

```
mkdir -p /opt/oracle  
wget  
https://download.oracle.com/otn_software/linux/instantclient/19800/instantclient  
-basic-linux.x64-19.8.0.0.0dbru.zip  
wget  
https://download.oracle.com/otn_software/linux/instantclient/19800/instantclient  
-sqlplus-linux.x64-19.8.0.0.0dbru.zip  
rm -fr /opt/oracle/*  
unzip instantclient-basic-linux.x64-19.8.0.0.0dbru.zip -d /opt/oracle/  
unzip instantclient-sqlplus-linux.x64-19.8.0.0.0dbru.zip -d /opt/oracle/
```

```
cat>> /root/.profile <<'EOF_ENV'  
#!/bin/bash  
VERSION=19.8  
export PATH=$PATH:/opt/oracle/instantclient_19_8  
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/opt/oracle/instantclient_19_8  
export ORACLE_HOME=/opt/oracle/instantclient_19_8  
EOF_ENV
```

```
source '/root/.profile'
```

IPAM Dependencies

```
apt install -y \  
xprobe libnetaddr-ip-perl \  
coreutils libdbd-mysql-perl \  
libxml-simple-perl libgeo-ip-perl \  
libio-socket-inet6-perl libxml-twig-perl \  
libnetaddr-ip-perl
```

ODBC dependencies for MS SQL

```
curl -sSL https://packages.microsoft.com/keys/microsoft.asc | \  
tee /etc/apt/trusted.gpg.d/microsoft.asc  
curl -sSL https://packages.microsoft.com/config/ubuntu/20.04/prod.list | \  
tee /etc/apt/sources.list.d/microsoft-prod.list  
apt update  
env ACCEPT_EULA=Y apt install -y msodbcsql17
```

AppArmor and UFW Configuration

```
systemctl stop ufw.service  
systemctl disable ufw  
systemctl stop apparmor  
systemctl disable apparmor
```

MySQL Installation

```
curl -O https://repo.percona.com/apt/percona-release_latest.generic_all.deb  
apt install -y gnupg2 lsb-release ./percona-release_latest.generic_all.deb  
percona-release setup ps80  
apt install -y percona-server-server percona-xtrabackup-80
```

```
systemctl start mysql  
  
mysql -uroot -p  
  
ALTER USER 'root'@'localhost' IDENTIFIED WITH mysql_native_password BY  
'pandora';  
  
create database pandora;  
  
CREATE USER pandora IDENTIFIED BY 'pandora';  
  
ALTER USER 'pandora' IDENTIFIED WITH mysql_native_password BY 'pandora';  
  
GRANT ALL PRIVILEGES ON pandora.* TO 'pandora';  
  
exit;
```

```
cat > /etc/mysql/my.cnf << EOF_DB
[mysqld]
datadir=/var/lib/mysql
user=mysql
character-set-server=utf8mb4
skip-character-set-client-handshake
# Disabling symbolic-links is recommended to prevent assorted security risks
symbolic-links=0
# Mysql optimizations for Pandora FMS
# Please check the documentation in http://pandorafms.com for better results
max_allowed_packet = 64M
innodb_buffer_pool_size = grep -i total /proc/meminfo | head-1 | awk '{printf
 "%.2f \n", $(NF-1)*0.4/1024}' | sed "s/..*$/M/g"
innodb_lock_wait_timeout = 90
innodb_file_per_table
innodb_flush_log_at_trx_commit = 0
innodb_flush_method = O_DIRECT
innodb_log_file_size = 64M
innodb_log_buffer_size = 16M
innodb_io_capacity = 300
thread_cache_size = 8
thread_stack = 256K
max_connections = 100
key_buffer_size=4M
read_buffer_size=128K
read_rnd_buffer_size=128K
sort_buffer_size=128K
join_buffer_size=4M
skip-log-bin
sql_mode=""
log-error=/var/log/mysql/error.log
[mysqld_safe]
log-error=/var/log/mysqld.log
pid-file=/var/run/mysqld/mysqld.pid
EOF_DB
```

```
systemctl restart mysql
```

Installation of Pandora FMS

Download links for the PFMS server and Web Console installers can be requested [through this link](#) and get a free trial (if you already have a license you can access



through the [Warp Update On Line](#)).

```
wget  
https://firefly.pandorafms.com/pandorafms/LTS/pandorafms_one_agent_linux-lts.tar  
.gz
```

Installing the PFMS Web Console

In this case the latest LTS version (the file name may be different):

```
tar xvzf pandorafms_console-lts.src.tar.gz  
cp -Ra pandora_console /var/www/html/  
rm -f /var/www/html/pandora_console/*.spec
```

PFMS Server Installation

In this case the latest LTS version (the file name may be different):

```
useradd pandora  
  
mv pandorafms_server-7.0NG.tar.gz /opt/pandora/deploy/  
cd /opt/pandora/deploy  
tar xvfz pandorafms_server-lts.tar.gz  
cd pandora_server  
./pandora_server_installer --install
```

PFMS Agent Installation

```
apt install -y libyaml-tiny-perl perl coreutils wget curl unzip procps python3  
python3-pip  
  
mv pandorafms_agent_linux-7.0NG.tar.gz /opt/pandora/deploy/
```



```
cd /opt/pandora/deploy

tar xvzf pandorafms_one_agent_linux-lts.tar.gz

unix cd

./pandora_agent_installer --install

cp -a tentacle_client /usr/local/bin/
```

GoTTY Installation

```
cd /opt/pandora/deploy

wget https://firefly.pandorafms.com/pandorafms/utils/gotty_linux_amd64.tar.gz

tar xvzf gotty_linux_amd64.tar.gz

mv gotty /usr/bin/
```

Configuration for SSL

```
cat > /etc/apache2/conf-available/ssl-params.conf << EOF_PARAM
SSLCipherSuite EECDH+AESGCM:EDH+AESGCM:AES256+EECDH:AES256+EDH
    SSLProtocol All -SSLv2 -SSLv3 -TLSv1 -TLSv1.1
    SSLHonorCipherOrder On
    Header always set X-Frame-Options DENY
    Header always set X-Content-Type-Options nosniff
    # Requires Apache >= 2.4
    SSLCompression off
    SSLUseStapling on
    SSLStaplingCache "shmcb:logs/stapling-cache(150000)"
    # Requires Apache >= 2.4.11
    SSLSessionTickets Off
EOF_PARAM
```

```
a2enmod ssl
a2enmod headers
a2enmod rewrite
a2enconf ssl-params
a2ensite default-ssl
a2enconf ssl-params
apache2ctl configtest

systemctl restart apache2
```



```
systemctl enable mysql --now
systemctl enable apache2 --now
systemctl enable php8.0-fpm --now
```

Structure and data in MySQL

```
mysql -uroot -ppandora

wear pandora;

source /var/www/html/pandora_console/pandoradb.sql

source /var/www/html/pandora_console/pandoradb_data.sql

exit;
```

Configuring PHP and Apache2

```
cat > /var/www/html/pandora_console/include/config.php << EO_CONFIG_F
<?php
$config["dbtype"] = "mysql";
$config["dbname"]="pandora";
$config["dbuser"]="pandora";
$config["dbpass"]="pandora";
$config["dbhost"]="127.0.0.1";
$config["homedir"]="/var/www/html/pandora_console";
$config["homeurl"]="/pandora_console";
error_reporting(0);
$ownDir = dirname(__FILE__) . '/';
include ($ownDir . "config_process.php");
EO_CONFIG_F
```

```
cat > /etc/apache2/conf-enabled/pandora_security.conf << EO_CONFIG_F
ServerTokens Prod
<Directory "/var/www/html">
    Options FollowSymLinks
    AllowOverride All
    Require all granted
</Directory>
EO_CONFIG_F
```

```
chmod 600 /var/www/html/pandora_console/include/config.php
```



```
chown -R www-data:www-data /var/www/html/pandora_console
```

```
mv /var/www/html/pandora_console/install.php  
/var/www/html/pandora_console/install.done
```

```
ln -s /etc/php/8.0/fpm/php.ini /etc/
```

```
sed --follow-symlinks -i -e "s/^max_input_time.*/max_input_time = -1/g"  
/etc/php.ini
```

```
sed --follow-symlinks -i -e "s/^max_execution_time.*/max_execution_time = 0/g"  
/etc/php.ini
```

```
sed --follow-symlinks -i -e "s/^upload_max_filesize.*/upload_max_filesize =  
800M/g" /etc/php.ini
```

```
sed --follow-symlinks -i -e "s/^memory_limit.*/memory_limit = 800M/g"  
/etc/php.ini
```

```
sed --follow-symlinks -i -e "s/.*post_max_size =.*/post_max_size = 800M/"  
/etc/php.ini
```

```
sed --follow-symlinks -i -e "s/^disable_functions/;disable_functions/"  
/etc/php.ini
```

```
cat > /var/www/html/index.html << EOF_INDEX  
<meta HTTP-EQUIV="REFRESH" content="0; url=/pandora_console/">  
EOF_INDEX
```

```
systemctl restart apache2
```

```
systemctl restart php8.0-fpm
```

PFMS Agent and Server Configuration

```
cat> /etc/snmp/snmptrapd.conf <<EOF  
authCommunity log public  
disableAuthorization yes  
EOF
```

```
sed -i -e "s/^dbhost.*/dbhost 127.0.0.1/g" /etc/pandora/pandora_server.conf
```

```
sed -i -e "s/^dbname.*/dbname pandora/g" /etc/pandora/pandora_server.conf
```



```
sed -i -e "s/^dbuser.*/dbuser pandora/g" /etc/pandora/pandora_server.conf
sed -i -e "s|^dbpass.*|dbpass pandora|g" /etc/pandora/pandora_server.conf
sed -i -e "s/^dbport.*/dbport 3306/g" /etc/pandora/pandora_server.conf
sed -i -e "s/^#.mssql_driver.*/mssql_driver 17/g"
/etc/pandora/pandora_server.conf
```

```
grep -q "group www-data" /etc/pandora/pandora_server.conf || \
cat>> /etc/pandora/pandora_server.conf<<EOF_G
#Adding group www-data to assigning remote-config permission correctly for
ubuntu 22.04
group www-data
EOF_G
```

```
sed -i "s/^remote_config.*$/remote_config 1/g" /etc/pandora/pandora_agent.conf
```

```
cat> /etc/pandora/pandora_server.env <<'EOF_ENV'
#!/bin/bash
VERSION=19.8
export PATH=$PATH:/opt/oracle/instantclient_19_8
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/opt/oracle/instantclient_19_8
export ORACLE_HOME=/opt/oracle/instantclient_19_8
export OPENSSL_CONF=/etc/ssl
EOF_ENV
```

```
cat>> /etc/sysctl.conf <<EO_K0
# Pandora FMS Optimization
#default=5
net.ipv4.tcp_syn_retries = 3
#default=5
net.ipv4.tcp_synack_retries = 3
#default=1024
net.ipv4.tcp_max_syn_backlog = 65536
#default=124928
net.core.wmem_max = 8388608
#default=131071
net.core.rmem_max = 8388608
#default = 128
net.core.somaxconn = 1024

#default = 20480
net.core.optmem_max = 81920
```



E0_K0

```
sysctl --system
```

```
chown pandora: www-data /var/log/pandora
```

```
chmod g+s /var/log/pandora
```

```
cat> /etc/logrotate.d/pandora_server <<E0_LR
/var/log/pandora/pandora_server.log
/var/log/pandora/web_socket.log
/var/log/pandora/pandora_server.error {
    your apache root
    weekly
    missingok
    size 300000
    rotate 3
    max age 90
    compress
    notifempty
    copytruncate
    create 660 pandora apache
}
```

```
/var/log/pandora/pandora_snmptrap.log {
    your apache root
    weekly
    missingok
    size 500000
    rotate 1
    max age 30
    notifempty
    copytruncate
    create 660 pandora apache
}
```

E0_LR

```
cat> /etc/logrotate.d/pandora_agent <<E0_LRA
/var/log/pandora/pandora_agent.log {
    your apache root
    weekly
    missingok
    size 300000
    rotate 3
    max age 90
    compress
    notifempty
```



```
        copytruncate
    }

EO_LRA

chmod 0644 /etc/logrotate.d/pandora_server

chmod 0644 /etc/logrotate.d/pandora_agent
```

Tentacle and cron

```
systemctl start pandora_server

systemctl enable pandora_server

service tentacle_server start

systemctl enable tentacle_server
```

```
echo "* * * * * root wget -q -O - --no-check-certificate --load-cookies
/tmp/cron-session-cookies --save-cookies /tmp/cron-session-cookies --keep -
session-cookies http://127.0.0.1/pandora_console/enterprise/cron.php >>
$PANDORA_CONSOLE/log/cron.log" >> /etc/crontab

echo "@hourly root bash -c /etc/cron.hourly/pandora_db" >> /etc/crontab
```

Agent remote configuration:

```
sed -i "s/^remote_config.*$/remote_config 1/g" /etc/pandora/pandora_agent.conf

systemctl start pandora_agent_daemon

systemctl enable pandora_agent_daemon
```

If there was a problem with PhantomJS:

```
sed --follow-symlinks -i -e "s/^openssl_conf = openssl_init/#openssl_conf =
openssl_init/g" /etc/ssl/openssl.cnf
```



Login to PFMS

To access the Web Console, type the IP address (or URL) of the device followed by `/pandora_console/` .

The default login credentials are:

- user: admin
- password: pandora

[Back to Pandora FMS Documentation Index](#)