



# Rocky Linux への Pandora FMS インストールガイド



<https://pandorafms.com/manual/!current/>

Permanent link:

[https://pandorafms.com/manual/!current/ja/documentation/pandorafms/technical\\_annexes/31\\_pfms\\_install\\_latest\\_rocky\\_linux](https://pandorafms.com/manual/!current/ja/documentation/pandorafms/technical_annexes/31_pfms_install_latest_rocky_linux)  
2025/03/04 21:28



# Rocky Linux への Pandora FMS インストールガイド

[Pandora FMS ドキュメント一覧に戻る](#)

## 前提条件

- Rocky Linux 8 と root 権限
- インターネット接続

## リポジトリ設定

```
dnf install -y \  
epel-release \  
tar \  
dnf-utils \  
http://rpms.remirepo.net/enterprise/remi-release-8.rpm
```

```
dnf module reset php  
  
dnf module install -y php:remi-8.2  
  
dnf config-manager --set-enabled powertools
```

## Percona データベースインストール

```
dnf install -y https://repo.percona.com/yum/percona-release-latest.noarch.rpm  
  
dnf module disable -y mysql  
  
rm -rf /etc/my.cnf  
  
percona-release setup ps80 -y  
  
dnf install -y percona-server-server percona-xtrabackup-80
```

## Web コンソール依存ファイルのインストール

```
dnf install -y \  
  php \  
  postfix \  
  php-mcrypt \  
  php-cli \  
  php-gd \  
  php-curl \  
  php-session \  
  php-mysqlnd \  
  php-ldap \  
  php-zip \  
  php-zlib \  
  php-fileinfo \  
  php-gettext \  
  php-snmp \  
  php-mbstring \  
  php-pecl-zip \  
  php-xmlrpc \  
  php-fpm \  
  php-xml \  
  php-yaml \  
  libxslt \  
  wget \  
  httpd \  
  mod_php \  
  atk \  
  avahi-libs \  
  cairo \  
  cups-libs \  
  fribidi \  
  gd \  
  gdk-pixbuf2 \  
  ghostscript \  
  graphite2 \  
  graphviz \  
  gtk2 \  
  harfbuzz \  
  hicolor-icon-theme \  
  hwdata \  
  jasper-libs \  
  lcms2 \  
  libICE \  
  libSM \  
  libXaw \  
  libXcomposite \  
  libXcursor \  
  libXdamage \  
  libXext \  
  libXfixes \  

```

```
libXft \  
libXi \  
libXinerama \  
libXmu \  
libXrandr \  
libXrender \  
libXt \  
libXxf86vm \  
libcroco \  
libdrm \  
libfontenc \  
libglvnd \  
libglvnd-egl \  
libglvnd-glx \  
libpciaccess \  
librsvg2 \  
libthai \  
libtool-ltdl \  
libwayland-client \  
libwayland-server \  
libxshmfence \  
mesa-libEGL \  
mesa-libGL \  
mesa-libgbm \  
mesa-libglapi \  
pango \  
pixman \  
xorg-x11-fonts-75dpi \  
xorg-x11-fonts-misc \  
poppler-data \  
mod_ssl \  
libzstd \  
openldap-clients \  
https://firefly.pandorafms.com/centos8/chromium-122.0.6261.128-1.el8.x86\_64.rpm \  
  https://firefly.pandorafms.com/centos8/chromium-common-122.0.6261.128-1.el8.x86\_64.rpm \  
  http://firefly.pandorafms.com/centos8/perl-Net-Telnet-3.04-1.el8.noarch.rpm \  
  http://firefly.pandorafms.com/centos7/wmic-1.4-1.el7.x86\_64.rpm
```

## Pandora FMS サーバ依存ファイルのインストール

```
dnf install -y \  
  perl \  
  vim \  
  fping \  
  perl-IO-Compress \  
  nmap \  

```

```
sudo \  
perl-Time-HiRes \  
nfdump \  
net-snmp-utils \  
'perl(NetAddr::IP)' \  
'perl(Sys::Syslog)' \  
'perl(DBI)' \  
'perl(XML::Simple)' \  
'perl(Geo::IP)' \  
'perl(IO::Socket::INET6)' \  
'perl(XML::Twig)' \  
expect \  
openssh-clients \  
java \  
bind-utils \  
whois \  
libnsl \  
http://firefly.pandorafms.com/centos7/xprobe2-0.3-12.2.x86\_64.rpm \  
http://firefly.pandorafms.com/centos7/wmic-1.4-1.el7.x86\_64.rpm \  
https://firefly.pandorafms.com/centos8/pandorawmic-1.0.0-1.x86\_64.rpm
```

## Perl および VMware 依存ファイル

```
dnf install -y \  
perl-Net-HTTP \  
perl-libwww-perl \  
openssl-devel \  
perl-Crypt-CBC \  
perl-Bytes-Random-Secure \  
perl-Crypt-Random-Seed \  
perl-Math-Random-ISAAC \  
perl-JSON \  
perl-Crypt-SSLeay \  
http://firefly.pandorafms.com/centos8/perl-Crypt-OpenSSL-AES-0.02-1.el8.x86\_64.r  
pm \  
http://firefly.pandorafms.com/centos8/VMware-vSphere-Perl-SDK-6.5.0-4566394.x86\_64.rpm
```

## Oracle Client インストール

```
dnf install -y \  
https://download.oracle.com/otn\_software/linux/instantclient/19800/oracle-instantclient19.8-basic-19.8.0.0.0-1.x86\_64.rpm \  
https://download.oracle.com/otn\_software/linux/instantclient/19800/oracle-instantclient19.8-sqlplus-19.8.0.0.0-1.x86\_64.rpm
```

## Pandora FMS 自動検出のための依存ファイルインストール

```
curl https://packages.microsoft.com/config/rhel/8/prod.repo -o
/etc/yum.repos.d/mssql-release.repo

dnf remove unixODBC-utf16 unixODBC-utf16-devel

env ACCEPT_EULA=Y dnf install -y msodbcsql17
```

## オペレーティングシステム設定とデータベース作成

```
setenforce 0

sed -i -e "s/^SELINUX=.*SELINUX=disabled/g" /etc/selinux/config

systemctl disable firewalld --now
```

```
cat> /etc/my.cnf <<EO_CONFIG_TMP
[mysqld]
datadir=/var/lib/mysql
socket=/var/lib/mysql/mysql.sock
symbolic-links=0
log-error=/var/log/mysql.log
pid-file=/var/run/mysql/mysql.pid
EO_CONFIG_TMP
```

```
systemctl start mysqld

grep "temporary password" /var/log/mysql.log | rev | cut -d' ' -f1 | rev
mysql -uroot -p"password";

SET PASSWORD FOR 'root'@'localhost' = 'Pandora4!';

UNINSTALL COMPONENT 'file:///component_validate_password';

SET PASSWORD FOR 'root'@'localhost' = 'pandora';

CREATE DATABASE pandora;

CREATE USER 'pandora'@'%' IDENTIFIED BY 'pandora';
```

```
ALTER USER 'pandora'@'%' IDENTIFIED WITH mysql_native_password BY 'pandora';
GRANT ALL PRIVILEGES ON pandora.* TO 'pandora'@'%';
```

```
exit
```

```
POOL_SIZE=$(grep -i total /proc/meminfo | head -1 | awk '{printf "%.2f \n",
$(NF-1)*0.4/1024}' | sed "s/\\.. *$/M/g")
```

```
cat> /etc/my.cnf <<EO_CONFIG_F
[mysqld]
datadir=/var/lib/mysql
socket=/var/lib/mysql/mysql.sock
user=mysql
character-set-server=utf8mb4
skip-character-set-client-handshake
# Disabling symbolic-links is recommended to prevent assorted security risks
symbolic-links=0
# Mysql optimizations for Pandora FMS
# Please check the documentation in http://pandorafms.com for better results
```

```
max_allowed_packet = 64M
innodb_buffer_pool_size = $POOL_SIZE
innodb_lock_wait_timeout = 90
innodb_file_per_table
innodb_flush_log_at_trx_commit = 0
innodb_flush_method = O_DIRECT
innodb_log_file_size = 64M
innodb_log_buffer_size = 16M
innodb_io_capacity = 300
thread_cache_size = 8
thread_stack = 256K
max_connections = 100
```

```
key_buffer_size=4M
read_buffer_size=128K
read_rnd_buffer_size=128K
sort_buffer_size=128K
join_buffer_size=4M
```

```
skip-log-bin
```

```
sql_mode=""
```

```
[mysqld_safe]
log-error=/var/log/mysql.log
pid-file=/var/run/mysql/mysql.pid
```

```
EO_CONFIG_F
```



```
systemctl restart mysqld  
systemctl enable mysqld --now
```

## コンソールと Pandora FMS サーバのインストール

PFMS サーバ および Web コンソールインストーラーのダウンロードリンクは [こちら](#) からリクエストでき、無料トライアル (デモ) を入手できます。

PFMS ソフトウェアエージェントをインストールするには:

```
wget  
https://firefly.pandorafms.com/pandorafms/latest/pandorafms_one_agent_linux_bin-  
latest.el8.x86_64.rpm
```

```
dnf install -y ./pandorafms*.rpm
```

```
wget https://firefly.pandorafms.com/pandorafms/utils/gotty_linux_amd64.tar.gz  
tar xvzf gotty_linux_amd64.tar.gz  
mv gotty /usr/bin/
```

```
systemctl enable mysqld --now  
systemctl enable httpd --now
```

```
mysql -upandora -ppandora
```

```
use pandora;
```

```
source /var/www/html/pandora_console/pandoradb.sql;

source /var/www/html/pandora_console/pandoradb_data.sql;

exit;
```

```
cat> /var/www/html/pandora_console/include/config.php <<EO_CONFIG_F
<?php
$config["dbtype"] = "mysql";
$config["dbname"]="pandora";
$config["dbuser"]="pandora";
$config["dbpass"]="pandora";
$config["dbhost"]="127.0.0.1";
$config["homedir"]="/var/www/html/pandora_console";
$config["homeurl"]="/pandora_console";
error_reporting(0);
$ownDir = dirname(__FILE__) . '/';
include (\$ownDir . "config_process.php");
EO_CONFIG_F
```

```
cat> /etc/httpd/conf.d/pandora.conf <<EO_CONFIG_F
ServerTokens Prod
<Directory "/var/www/html">
    Options FollowSymLinks
    AllowOverride All
    Require all granted
</Directory>
EO_CONFIG_F
```

```
sed -i -e "s/php_flag engine off//g"
/var/www/html/pandora_console/images/.htaccess

sed -i -e "s/php_flag engine off//g"
/var/www/html/pandora_console/attachment/.htaccess
```

```
chmod 600 /var/www/html/pandora_console/include/config.php

chown apache. /var/www/html/pandora_console/include/config.php

mv /var/www/html/pandora_console/install.php
/var/www/html/pandora_console/install.done
```

```
sed -i -e "s/^max_input_time.*/max_input_time = -1/g" /etc/php.ini
sed -i -e "s/^max_execution_time.*/max_execution_time = 0/g" /etc/php.ini
sed -i -e "s/^upload_max_filesize.*/upload_max_filesize = 800M/g" /etc/php.ini
sed -i -e "s/^memory_limit.*/memory_limit = 800M/g" /etc/php.ini
sed -i -e "s/.*post_max_size =.*/post_max_size = 800M/" /etc/php.ini
```

---

```
echo 'Timeout 900'> /etc/httpd/conf.d/timeout.conf

cat> /var/www/html/index.html <<EOF_INDEX
<meta HTTP-EQUIV="REFRESH" content="0; url=/pandora_console/">
EOF_INDEX
```

---

```
systemctl restart httpd

systemctl restart php-fpm
```

---

```
cat> /etc/snmp/snmptrapd.conf <<EOF
authCommunity log public
disableAuthorization yes
EOF
```

---

```
sed -i -e "s/^dbhost.*/dbhost 127.0.0.1/g" /etc/pandora/pandora_server.conf
sed -i -e "s/^dbname.*/dbname pandora/g" /etc/pandora/pandora_server.conf
sed -i -e "s/^dbuser.*/dbuser pandora/g" /etc/pandora/pandora_server.conf
sed -i -e "s|^dbpass.*|dbpass pandora|g" /etc/pandora/pandora_server.conf
sed -i -e "s/^dbport.*/dbport 3306/g" /etc/pandora/pandora_server.conf
sed -i -e "s/^#.mssql_driver.*/mssql_driver ODBC Driver 17 for SQL Server/g"
/etc/pandora/pandora_server.conf
```

---

```
sed -i -e "s|^fping.*|fping /usr/sbin/fping|g" /etc/pandora/pandora_server.conf
```

---

```
sed -i "s/^remote_config.*$/remote_config 1/g" /etc/pandora/pandora_server.conf
```

---

```
cat> /etc/pandora/pandora_server.env <<'EOF_ENV'  
#!/bin/bash  
VERSION=19.8  
export PATH=$PATH:$HOME/bin:/usr/lib/oracle/$VERSION/client64/bin  
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/usr/lib/oracle/$VERSION/client64/lib  
export ORACLE_HOME=/usr/lib/oracle/$VERSION/client64  
EOF_ENV
```

---

```
cat>> /etc/sysctl.conf <<EO_KO  
# Pandora FMS Optimization  
  
# default=5  
net.ipv4.tcp_syn_retries = 3  
  
# default=5  
net.ipv4.tcp_synack_retries = 3  
  
# default=1024  
net.ipv4.tcp_max_syn_backlog = 65536  
  
# default=124928  
net.core.wmem_max = 8388608  
  
# default=131071  
net.core.rmem_max = 8388608  
  
# default = 128  
net.core.somaxconn = 1024  
  
# default = 20480  
net.core.optmem_max = 81920  
  
EO_KO
```

---

```
sysctl --system  
  
chown pandora:apache /var/log/pandora  
  
chmod g+s /var/log/pandora
```

---

```
cat> /etc/logrotate.d/pandora_server <<EO_LR  
/var/log/pandora/pandora_server.log
```

```
/var/log/pandora/web_socket.log
/var/log/pandora/pandora_server.error {
    su root apache
    weekly
    missingok
    size 300000
    rotate 3
    maxage 90
    compress
    notifempty
    copytruncate
    create 660 pandora apache
}

/var/log/pandora/pandora_snmptrap.log {
    su root apache
    weekly
    missingok
    size 500000
    rotate 1
    maxage 30
    notifempty
    copytruncate
    create 660 pandora apache
}

EO_LR

cat> /etc/logrotate.d/pandora_agent <<EO_LRA
/var/log/pandora/pandora_agent.log {
    su root apache
    weekly
    missingok
    size 300000
    rotate 3
    maxage 90
    compress
    notifempty
    copytruncate
}

EO_LRA
```

---

```
chmod 0644 /etc/logrotate.d/pandora_server
```

```
chmod 0644 /etc/logrotate.d/pandora_agent
```

---

```
systemctl enable pandora_server --now
```

```
systemctl start pandora_server  
systemctl enable tentacle_serverd  
service tentacle_serverd start
```

---

```
echo \"* * * * * root wget -q -O - --no-check-certificate --load-cookies  
/tmp/cron-session-cookies --save-cookies /tmp/cron-session-cookies --keep  
session-cookies http://127.0.0.1/pandora_console/enterprise/cron.php>>  
/var/www/html/pandora_console/log/cron.log\">> /etc/crontab
```

---

```
systemctl enable pandora_agent_daemon  
systemctl start pandora_agent_daemon
```

---

## Pandora FMS へのログイン

Web コンソールにアクセスするには、デバイスの IP アドレス (または URL) に続けて /pandora\_console/ を入力します。

デフォルトのログイン情報は次の通りです。

- ユーザ: admin
- パスワード: pandora

[Pandora FMS ドキュメント一覧に戻る](#)